



# Test Report : MDS02N-15

---

2W SIP Package DC-DC Medical Grade Unregulated Converter

## ■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

## ■ SAFETY TEST

Safety Test

## ■ RELIABILITY TEST

Environment Test

Other Test

**DESIGN VERIFY TEST**
**OUTPUT FUNCTION TEST**

| NO | TEST ITEM        | SPECICATION       | TEST CONDITION                                  | RESULT            | VERDICT |
|----|------------------|-------------------|---|-------------------|---------|
| 1  | VOLTAGE ACCURACY | -5%~+5% (Max)     | I/P:24VDC<br>O/P:FULL LOAD<br>Ta:25°C           | +1.77%            | P       |
| 2  | RIPPLE & NOISE   | 75 mVp-p (Max)    | I/P:24VDC<br>O/P:FULL LOAD<br>Ta:25°C           | 41mV              | P       |
| 3  | LINE REGULATION  | -12% ~ +12% (Max) | I/P:21.6VDC~26.4VDC<br>O/P:FULL LOAD<br>Ta:25°C | -10.51% ~ +10.56% | P       |
| 4  | LOAD REGULATION  | -10% ~ +10% (Max) | I/P:24VDC<br>O/P:MINI LOAD-FULL LOAD<br>Ta:25°C | -2.34% ~ +2.51%   | P       |

**INPUT FUNCTION TEST**

| NO | TEST ITEM  | SPECICATION                                      | TEST CONDITION                             | RESULT                                  | VERDICT |
|----|------------|--|--|---|---------|
| 1  | EFFICIENCY | 85 % (Typ)                                       | I/P:24VDC<br>O/P:FULL LOAD<br>Ta:25°C      | 85.67%                                  | P       |
| 2  | DC CURRENT | 100 mA / FULL LOAD (Max)<br>9 mA / NO LOAD (Max) | I/P:24VDC<br>O/P:NO / FULL LOAD<br>Ta:25°C | 96.88mA / FULL LOAD<br>7.58mA / NO LOAD | P       |

**PROTECTION FUNCTION TEST**

| NO | TEST ITEM        | SPECICATION         | TEST CONDITION                        | RESULT          | VERDICT |
|----|------------------|---------------------|---------------------------------------|-----------------|---------|
| 1  | SHORT PROTECTION | MOMENTARY 3sec. max | I/P:24VDC<br>O/P:FULL LOAD<br>Ta:25°C | NO DAMAGE<br>OK | P       |

**SAFETY TEST**
**SAFETY TEST**

| NO | TEST ITEM         | SPECICATION          | TEST CONDITION                  | RESULT                        | VERDICT |
|----|-------------------|----------------------|---------------------------------|-------------------------------|---------|
| 1  | WITHSTAND VOLTAGE | I/P-O/P:6000 VDC/min | I/P-O/P:6000 VDC/min<br>Ta:25°C | I/P-O/P: 0.002mA<br>NO DAMAGE | P       |

|   |                      |                      |                            |                            |   |
|---|----------------------|----------------------|----------------------------|----------------------------|---|
| 2 | ISOLATION RESISTANCE | I/P-O/P:500VDC>100MΩ | I/P-O/P:500 VDC<br>Ta:25°C | I/P-O/P>100MΩ<br>NO DAMAGE | P |
|---|----------------------|----------------------|----------------------------|----------------------------|---|

## ■ RELIABILITY TEST

### ENVIRONMENT TEST

| NO | TEST ITEM                    | SPECICATION   | TEST CONDITION                           | RESULT    | VERDICT  |   |   |   |      |        |         |  |  |
|----|------------------------------|---|--|-----------|----------|---|---|---|------|--------|---------|--|--|
| 1  | TEMPERATURE RISE TEST        | 1. ROOM AMBIENT BURN-IN : 8 HRS<br>I/P:24VDC O/P:FULL LOAD Ta=25°C<br>2. HIGH AMBIENT BURN-IN : 8 HRS<br>I/P:24VDC O/P:FULL LOAD Ta=85°C  |  |           | P        |   |   |   |      |        |         |  |  |
|    |                              | <table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>1</th> <th>2</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>CASE</td> <td>39.0°C</td> <td>100.3°C</td> </tr> </tbody> </table> |  | NO        | Position | 1 | 2 | 1 | CASE | 39.0°C | 100.3°C |  |  |
| NO | Position                     | 1   | 2  |           |          |   |   |   |      |        |         |  |  |
| 1  | CASE                         | 39.0°C  | 100.3°C                                  |           |          |   |   |   |      |        |         |  |  |
| 2  | LOW TEMPERATURE TURN ON TEST | TURN ON AFTER 2 HOURS   | I/P:24VDC<br>O/P: FULL LOAD<br>Ta= -40°C | TEST : OK | P        |   |   |   |      |        |         |  |  |

### OTHER

| NO | TEST ITEM | SPECICATION   | TEST CONDITION | RESULT | VERDICT |
|----|-----------|---|----------------|--------|---------|
| 1  | MTBF      | MIL-HDBK-217F,GB,25°C,Full Load<br>TOTAL FAILURE RATE : 0.243962<br>M.T.B.F : 4099000 HRS |                |        | P       |

| TEST RESULT | TESTER | APPROVAL     |
|-------------|--------|--------------|
| PASS        | ARCHEN | VINCENT ZENG |