

CERTIFICATE

Issued to:
Applicant:
MEAN WELL Enterprises Co., Ltd.
No.28, Wuquan 3rd Rd, Wugu District
24891 New Taipei City, Taiwan

Licensee:
MEAN WELL Enterprises Co., Ltd.
No.28, Wuquan 3rd Rd, Wugu District
24891 New Taipei City, Taiwan

Product : Independent LED controlgears
Trade name(s) : MEAN WELL
Type(s)/model(s) : NPF-xy-z, PWM-x-y, PWM-60-yDA, PWM-60-yDA2, PWM-60-xyzz

The product and any acceptable variation thereto is specified in the Annex to this certificate and the documents therein referred to.

DEKRA hereby declares that the above-mentioned product has been certified on the basis of:

- a type test according to the standard EN 61347-1:2015, EN 61347-2-13:2014, EN 61347-2-13:2014/A1:2017, EN 62384:2006 and EN 62384:2006/A1:2009
- an inspection of the production location according to CENELEC Operational Document CIG 021
- a certification agreement with the number 2175773


DEKRA hereby grants the right to use the ENEC certification mark.

The ENEC certification mark may be applied to the product as specified in this certificate for the duration of the ENEC certification agreement and under the conditions of the ENEC certification agreement.

This certificate is issued on 1 December 2020 and expires upon withdrawal of one of the above mentioned standards.

Certificate number: 35-116654

DEKRA Certification B.V.



B.T.M. Holtus
Managing Director



K. Lin
Certification Manager

© Integral publication of this certificate is allowed

ACCREDITED BY THE
DUTCH ACCREDITATION
COUNCIL



SPECIFICATION OF THE CERTIFIED PRODUCT**Product data**

Product	: Independent LED controlgears
Trade name(s)	: MEAN WELL
Type(s)/model(s)	: NPF-40-12, NPF-40-15, NPF-40-20, NPF-40-24, NPF-40-30, NPF-40-36, NPF-40-42, NPF-40-48, NPF-40-54, NPF-40D-12, NPF-40D-15, NPF-40D-20, NPF-40D-24, NPF-40D-30, NPF-40D-36, NPF-40D-42, NPF-40D-48, NPF-40D-54, NPF-60-12, NPF-60-15, NPF-60-20, NPF-60-24, NPF-60-30, NPF-60-36, NPF-60-42, NPF-60-48, NPF-60-54, NPF-60D-12, NPF-60D-15, NPF-60D-20, NPF-60D-24, NPF-60D-30, NPF-60D-36, NPF-60D-42, NPF-60D-48, NPF-60D-54, PWM-40-12, PWM-40-24, PWM-40-36, PWM-40-48, PWM-60-12, PWM-60-12DA, PWM-60-12DA2, PWM-60-12KNBSTzz, PWM-60-12KNzz, PWM-60-24, PWM-60-24DA, PWM-60-24DA2, PWM-60-24KNBSTzz, PWM-60-24KNzz, PWM-60-36 and PWM-60-48
Rated input voltage	: 100-240 V~
Rated frequency	: 50/60 Hz
Class of insulation	: Class II
Power factor	: 0,95
Max. case temperature (tc)	: 85 °C
Ambient temperature (ta)	: 50 °C
Additional information	: Independent SELV, thermal protection: 110 °C, constant voltage type, MM mark, EL mark (only for PWM-60-12DA2, PWM-60-24 DA2)

Product data – type NPF-40-12, NPF-40D-12 and PWM-40-12

Rated input current	: 0,6 A
Degree of protection	: IP67
Output rating	: 12 Vdc, 3,34 A

Product data – type NPF-40-15 and NPF-40D-15

Rated input current	: 0,6 A
Degree of protection	: IP67
Output rating	: 15 Vdc, 2,67 A

Product data – type NPF-40-20 and NPF-40D-20

Rated input current	: 0,6 A
Degree of protection	: IP67
Output rating	: 20 Vdc, 2,0 A

Product data – type NPF-40-24, NPF-40D-24 and PWM-40-24

Rated input current	: 0,6 A
Degree of protection	: IP67
Output rating	: 24 Vdc, 1,67 A

Product data – type NPF-40-30 and NPF-40D-30

Rated input current	: 0,6 A
Degree of protection	: IP67
Output rating	: 30 Vdc, 1,34 A

Product data – type NPF-40-36, NPF-40D-36 and PWM-40-36

Rated input current : 0,6 A
Degree of protection : IP67
Output rating : 36 Vdc, 1,12 A

Product data – type NPF-40-42 and NPF-40D-42

Rated input current : 0,6 A
Degree of protection : IP67
Output rating : 42 Vdc, 0,96 A

Product data – type NPF-40-48, NPF-40D-48 and PWM-40-48

Rated input current : 0,6 A
Degree of protection : IP67
Output rating : 48 Vdc, 0,84 A

Product data – type NPF-40-54 and NPF-40D-54

Rated input current : 0,6 A
Degree of protection : IP67
Output rating : 54 Vdc, 0,76 A

Product data – type NPF-60-12, NPF-60D-12, PWM-60-12, PWM-60-12DA and PWM-60-12DA2

Rated input current : 0,8 A
Degree of protection : IP67
Output rating : 12 Vdc, 5,0 A

Product data – type NPF-60-15 and NPF-60D-15

Rated input current : 0,8 A
Degree of protection : IP67
Output rating : 15 Vdc, 4,0 A

Product data – type NPF-60-20 and NPF-60D-20

Rated input current : 0,8 A
Degree of protection : IP67
Output rating : 20 Vdc, 3,0 A

Product data – type NPF-60-24, NPF-60D-24, PWM-60-24, PWM-60-24DA and PWM-60-24DA2

Rated input current : 0,8 A
Degree of protection : IP67
Output rating : 24 Vdc, 2,5 A

Product data – type NPF-60-30 and NPF-60D-30

Rated input current : 0,8 A
Degree of protection : IP67
Output rating : 30 Vdc, 2,0 A

Product data – type NPF-60-36, NPF-60D-36 and PWM-60-36

Rated input current : 0,8 A
Degree of protection : IP67
Output rating : 36 Vdc, 1,67 A

Product data – type NPF-60-42 and NPF-60D-42

Rated input current : 0,8 A
Degree of protection : IP67
Output rating : 42 Vdc, 1,43 A

Product data – type NPF-60-48, NPF-60D-48 and PWM-60-48

Rated input current : 0,8 A
Degree of protection : IP67
Output rating : 48 Vdc, 1,25 A

Product data – type NPF-60-54 and NPF-60D-54

Rated input current : 0,8 A
Degree of protection : IP67
Output rating : 54 Vdc, 1,12 A

Product data – type PWM-60-12KNBSTzz and PWM-60-12KNzz

Rated input current : 0,8 A
Degree of protection : IP20
Output rating : 12 Vdc, 5,0 A

Product data – type PWM-60-24KNBSTzz and PWM-60-24KNzz

Rated input current : 0,8 A
Degree of protection : IP20
Output rating : 24 Vdc, 2,5 A

TESTS**Test requirements**

EN 61347-1:2015
EN 61347-2-13:2014
EN 61347-2-13:2014/A1:2017
EN 62384:2006
EN 62384:2006/A1:2009

Test result

The test results are laid down in DEKRA test file 436805800.

Additional information

Note:

1) NPF-xy-z:

The "x" in the model name can be 40 or 60 to denote output wattage in watt;

The "y" in the model name can be D or blank to denote with dimming function (D) or without (blank);

The "z" in the model name can be 12, 15, 20, 24, 30, 36, 42, 48 or 54 to denote output voltage in volt.

2) PWM-x-y:

The "x" in the model name can be 40 or 60 to denote output wattage in watt;

The "y" in the models name can be 12, 24, 36 or 48 to denote output voltage in volt.

3) PWM-60-yDA, PWM-60-yDA2:

The "y" in the models name can be 12 or 24 to denote output voltage in volt.

4) PWM-60-xyzz

The "x" in the models name can be 12 or 24 to denote output voltage in volt.

The "y" in the models name can be KN or KNBST to denote with or without connector on KNX dimming wire.

The "z" in the models name can be blank, 0-9 or A to Z, denote different encryption protocol for KNX program.

This certificate replaces certificate No. 35-112094 which we hereby declare invalid.

The list of components is laid down in test report 4368058.50, 4368058.51.

Conclusion

The examination proved that all requirements were met.

Factory location

MEAN WELL (GUANGZHOU) Electronics Co.,Ltd. Huadu Branch
No.11 Jingu South Road, Huadong Town, Huadu District,
Guangzhou 510890, Guangdong, China

Trade name : MEAN WELL stands for

